



### ➤ AvCarb® Gas Diffusion Systems for Fuel Cells

AvCarb Material Solution's series of AvCarb Gas Diffusion Systems combine BMP's proprietary carbon fiber paper, a PTFE treatment, and micro-porous layer coating, each designed for the rigorous demands of specific fuel cell applications such as PEMFC, DMFC, and PAFC.

AvCarb Gas Diffusion Systems are based upon carbon fiber paper. AvCarb carbon fabrics and AvCarb Molded Graphite Laminates treated with PTFE and micro-porous layers for fuel cell applications are also available.

Please consult our GDL product selection guide for help in identifying the optimal GDL design for your application.

#### ➤ PRODUCT BENEFITS

- Optimized fuel cell performance by application
- Gas permeability
- Conductivity
- Physical property uniformity
- Cost effective, high volume manufacturing methods

#### ➤ PRODUCT AVAILABILITY

##### Rolls:

- 400 mm or 800 mm width
- 10 - 800 m length
- Cores 6" / 152 mm ID

Cut sheets, samples available upon request



AvCarb Gas Diffusion Systems are fuel cell gas diffusion layers combining a carbon fiber paper substrate, a PTFE coating, and a surface microporous layer of PTFE and carbon particles. The table below lists nominal properties of commercially available AvCarb Gas Diffusion Systems, which have been engineered for optimal performance for selected fuel cell applications.

For assistance in selecting the right GDS product for your application, please refer to the AvCarb Gas Diffusion Layer Selection Guide, or contact us.

TYPICAL PROPERTY	UNITS	AvCarb GDS3215	AvCarb GDS3250	AvCarb GDS3260	AvCarb GDS2230	AvCarb GDS2240	AvCarb GDS22100	AvCarb GDS2120	AvCarb GDS1120
<b>Base Material</b>		AvCarb EP40	AvCarb EP40	AvCarb EP40	AvCarb P75	AvCarb P75	AvCarb P75	AvCarb P75	AvCarb P50
<b>Nominal Thickness</b> (@ 5.00 N/cm <sup>2</sup> )	microns	200	225	210	275	275	330	248	184
<b>Nominal Basis Weight</b>	g/m <sup>2</sup>	60	75	80	98	110	185	101	79
<b>Break Strength</b>									
machine direction	MPa	12.0	12.0	14.0	6.5	8.5	8.0	25.0	18.0
cross machine direction	MPa	5.0	7.0	8.5	4.0	5.5	5.0	15.0	10.0
<b>Stiffness</b>									
machine direction	Taber	12.0	10.0	10.0	22.0	22.0		21.0	10.0
cross machine direction	Taber	5.0	8.0	8.0	20.0	20.0	18.0	14.7	6.0
<b>Bulk Density</b> (@ 0.69 N/cm <sup>2</sup> / 1psi)	g/cm <sup>3</sup>	0.30	0.33	0.38	0.35	0.40	0.53	0.40	0.40
<b>Compressibility</b> (22N - 113N)/22 x 100%	%	10.0	16.0	15.0	17.0	15.0	7.0	11.0	14.0
<b>Through-Plane Resistivity</b>	mOhm*cm <sup>2</sup>	<14.0	<14.0	<14.0	<14.0	<14.0	<17.0	<14.0	<14.5
<b>Typical Roll Width</b>	mm	400/800	400/800	400/800	400/800	400/800	400/800	400/800	400/800

Specifications and descriptions in this document were in effect at the time of publication. AvCarb Material Solutions reserves the right to change specifications, product appearance or to discontinue products at any time. (02/2013)

AvCarb® is a trademark of AvCarb Material Solutions.

**AvCarb Material Solutions**  
Two Industrial Avenue  
Lowell, MA 01851-5199 USA  
Susan.Noel@AvCarb.com

**TEL:** (+1) 978.934.7500  
**FAX:** (+1) 978.934.7590

[www.AvCarb.com](http://www.AvCarb.com)